

## Eccentric Reducer (Grooved) XGQT17

### Product Description

#### Product Certification

UL Listed / FM Approved

#### Material of Construction

Ductile Iron as per ASTM A536 Gr. 65 - 45 - 12

#### Pressure Rating

Test Pressure : 12.5 MPa

Max. Working Pressure : 2.5 MPa

Please note that as per FM 1920:2007 Sizes <= 150 mm are rated PN20 and > 150 mm are rated PN16

#### Nuts & Bolts

Heat Treated Carbon Steel as per ISO 898-1 Class 8.8

#### Finishing

Epoxy Red Paint RAL - 3000/3001



### Dimensions (in mm)

Nominal Size	Nominal Size (Inch)	Pipe O.D.	L
100×65	4×2.2/1	114.3×76.1	102
100×80	4×3	114.3×88.9	102
125×80	5×3	139.7×88.9	102
125×100	5×4	139.7×114.3	102
150×65	6×2.1/2	165.1×76.1	102
150×80	6×3	165.1×88.9	102
150×100	6×4	165.1×114.3	102
150×125	6×5	165.1×139.7	102
200×80	8×3	219.1×88.9	130
200×100	8×4	219.1×114.3	130
200×125	8×5	219.1×139.7	130
200×150	8×6	219.1×165.1	130

