SANT VALVES
SINCE 1953

I.B.R

ISO 9001 CERTIFIED COMPANY

Cap with Eccentric Hole -

Product Description

Product Certification
UL Listed / FM Approved (EX 26523)

Material of Construction
Ductile Iron as per ASTM A536 Gr. 65 – 45 – 12

Pressure Rating
Test Pressure : 12.5 MPa
Max. Working Pressure : 2.5 MPa
Please note that as per FM 1920:2007 Sizes <= 150 mm are rated PN20 and > 150 mm are rated PN16

Nuts & Bolts
Heat Treated Carbon Steel as per ISO 898-1 Class 8.8

Finishing
Epoxy Red Paint RAL – 3000/3001

Branch Outlets
Threaded Branch Outlets as per BSPT ISO 7-1

Dimensions (in mm)

Nominal Size	Nominal Size (Inch)	Pipe O.D.	L
65×25	2.1/2×1	76.1×33.7	23.5
65×40	2.1/2×1.1/2	76.1×48.3	23.5
80×25	3×1	88.9×33.7	23.5
80×40	3×1.1/2	88.9×48.3	23.5
80×50	3×2	88.9×60.3	23.5
100×25	4×1	114.3×33.7	25.4
100×40	4×1.1/2	114.3×48.3	25.4
100×50	4×2	114.3×60.3	25.4
125×40	5×1.1/2	139.7×60.3	25.4
125×50	5×2	139.7×60.3	25.4
150×40	60×1.1/2	165.1×48.3	25.4
200×40	8×1.1/2	219.1×48.3	30.2
200×50	8×2	219.1×60.3	30.2

Sant Valves Pvt. Ltd.
G.T.Road Bye Pass,
Jalandhar – 144012. Punjab. INDIA

https://www.santvalves.com

Phone : +91 181 5084693
Fax: +91 181 5062270
Email : info@santvalves.com