

SBM-2 Bronze Gate Valve Standard, Screwed

Product Description

HSN 84818030

Product : 'SBM' Bronze Gate Valve
Type of Pattern : Standard Pattern
Body Material cum Standard : GM (IS:318 Gr.LTB2)
Description : Screwed in Bonnet, Inside Screw, Non-Rising Stem
Type of Seat : Integral seat
Type of Wedge : Solid wedge
Trim : Cu-Alloy
Gland Packing : Expanded Pure Flexible Graphite
End Details : Screwed female BSP threads to BS 21.

Testing & Certification

Body Test Pressure : 30.60kg/cm²g Hyd. (435 lbs/inch²) Hyd.
Seat Test Pressure : 20.40kg/cm²g Hyd. (290 lbs/inch²) Hyd.

Our Works' Test Certificate is furnished with every supply.

Application

Water	Oil
-------	-----



Materials of Construction

Components	Materials	Specifications
Body, Bonnet, Wedge, Gland & Gland Nut	Leaded Tin Bronze	IS:318 Gr.LTB2
Stem	Forged Brass	IS:6912 FLB
Gland Packing	Expanded Pure Flexible Graphite	—
Handwheel	Cast Iron / Steel	IS:210 Gr.FG200
Screw & Washer for Handwheel	Mild Steel	—

Dimensions (in mm)



Nominal Size	Nominal Size (Inches)	F	H	W
8	1/4	43	90	50
10	3/8	43	95	50
15	1/2	54	100	60
20	3/4	60	125	60
25	1	65	135	65
32	1.1/4	75	145	80
40	1.1/2	83	160	80
50	2	92	185	90
65	2.1/2	105	215	105
80	3	125	265	115
100	4	140	310	145

Notes

- Product images are for illustration purposes only. Actual product may vary.
- Actual dimensions may change over time, due to continual design improvements. Please confirm before placing order.