

IBR-10A Bronze Asbestos Packed Water Level Gauge Screwed (IBR Approved)

Product Description

HSN 90261020

Product : 'SANT' Bronze Asbestos Packed Water Level Gauge
Type of Pattern : Standard Pattern
Body Material cum Standard : Bronze IBR 282(a)(iv) Gr.B
Description : Right Hand Type / Left Hand Type
Gland Packing : Lubricated Asbestos
End Details : Screwed male BSP Parallel threads to BS 21.

Testing & Certification

Hydraulic Test Pressure : 300 Psig.Hyd.
Working Pressure : Max.BOP 150 Psig.(10.54Kg/cm²)
Maximum Working Temperature: 225°C (435°F)

Test Certificate in Form III-C as per IBR is furnished with every supply.

Application

Water	Steam
-------	-------




Materials of Construction

Components	Materials	Specifications
Body, Plug, Cover Nuts, Drain Cock & Back Nuts	Bronze	IBR 282(a)(iv) Gr.B
Fastening Nut	Forged Brass	IS:6912 FLB
Packing	Lubricated Asbestos	—

Dimensions (in mm)

Nominal Size	Nominal Size (Inches)	A
10	3/8	102
15	1/2	102
16	5/8	125
20	3/4	125



Notes

- Product images are for illustration purposes only. Actual product may vary.
- Actual dimensions may change over time, due to continual design improvements. Please confirm before placing order.